



# CHESTNUT

P R O D U C T S


## FINISHING SCHOOL

### *Using Finishing Oil*

1



1 Finishing Oil is a blend of oils (including Tung Oil), solvent and dryers with added UV filters to help reduce fading and discolouration of brightly coloured timber. Finishing Oil is hard wearing and water resistant, ideal for use indoors and outdoors where a high level of protection is required. Oil finishes are also very flexible and will move with the timber rather than crack.




2

2 Apply Finishing Oil to unsealed wood, using a cloth or a brush. Apply fairly liberally and wipe off any surplus after about twenty minutes.



3

3 Finishing Oil makes a great lubricant for sanding so it is possible to sand the first coat whilst the oil is still wet; the slurry created can also fill minor holes if required. Wet sanding will give an exceptionally smooth surface, resulting in a brighter finish.



4

4 Leave each coat at least eight hours to fully dry before applying further coats. For best results sand lightly between each coat to ensure a smooth surface.



5

5 Apply further coats until you have achieved the gloss level you require; a bright gloss should be visible after about five coats.

*See our YouTube channel for more tips!*

*More information available from your local stockists or contact us at:*

PO Box 260, Stowmarket, IP14 9BX

Tel: 01473 890118

mailroom@chestnutproducts.co.uk

www.chestnutproducts.co.uk

