



# CHESTNUT

P R O D U C T S

FINISHING SCHOOL

## *Applying Cellulose Sanding Sealer - how, when and why.*

1



1 The most popular choice for Woodturners is still Cellulose Sanding Sealer. It binds the loose fibres of the timber together, gives a solid base for finishing and seals the open pores so that less top coat is needed, producing a more resilient final finish.



2 Prepare your work, then apply Cellulose Sanding Sealer with the lathe stopped. On small areas a cloth is ideal. Beware of using paper towel as this can leave bits behind which can spoil the finish. Safety Cloth is an ideal choice for application.



3 Apply sealer over the entire surface. It is quite forgiving and doesn't normally show lines where overcoated. Don't apply too much, you shouldn't leave puddles on the surface, just an even coat.



4 On larger areas use a brush (or spray equipment). A brush makes it easier to keep a wet edge. Don't flood the surface. Only one coat of sealer should be applied.



5 The sealer dries quickly and is normally ready to sand within minutes. Lightly smooth the sealer with a fine abrasive, before overcoating with any of the waxes, lacquers or polishes in our range. We do not recommend using oils on top of sealer.

*See our YouTube channel for more tips!*

*More information available from your local stockists or contact us at:*

PO Box 260, Stowmarket, IP14 9BX

Tel: 01473 890118

mailroom@chestnutproducts.co.uk

www.chestnutproducts.co.uk

